

	OFFICE OF THE MARION COURSECTION RECORD CORNER SECTION 18 TOWNSHIP_ DATE: 1-26-99 PARTY CHIEF: Wilcoxen CREW: TYPE OF MARKER: "broken" METHOD OF ESTABLISHMENT:	15 RANGE 5	Line of South Ray	Prospect St 1100 S
ш	IN. S.P.C. E ZONE, NAD 83 NAME: 15051802 N: 500337.1093(m) E: 69862.2235(m)	1.	2	## H
Franklin Rd 8000	Shooting area back stop Air-field	Section Line 8000 E +/- Line Section Line 8000 E +/- Field Area:	e of Prospect St 110	0 S

Original post set 1820 by John Hendricks with witnesses: 23" beech S 35 E 31 links, 20" beech N 18 E 3 links per Marion County Atlas pg. 11. Survye by Hosbrook 12-1-1884 called for stone per Warren Township Legal Survey Book pg. 33. 9-5-68 called stone, S Q corner of Sec. 7-15-5. 2-26-75 called stone. Excavated 9-24-87 and stone found at surface and Harrison set. Re-tied 1-26-99 by Wilcoxen.

	HC551802	
REF.	DISTANCE	DESCRIPTION
1.	72,00′	Railroad spike NW 24" oak 15"up
2.	45.20′	Railroad spike N 30" oak 12"up
3,	23.25′	Mag nail E post 60'up
4,	20.00′	Mag nail N post 60°up